

30 205

LADYLUX® L2

SINGLE-HANDLE PULL DOWN KITCHEN FAUCET TRIPLE SPRAY 1.75 GPM WITH TOUCH TECHNOLOGY

Pure Freude
an Wasser






STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- 16" Faucet height
- 8 9/16" Aerator height
- 9 3/16" Faucet reach
- Touch activation of water via skin contact
- 6 V lithium-battery supply (type CR-P2)
- CE approved and meets the requirements of IAPMO IGC 349-2017
- Automatic safety stop after 60 sec. (factory set)
- GROHE Magnetic Docking guarantees easy retraction and smooth docking of the spray head back to the starting position
- Pull-down spray with 3 spray types: laminar spray, shower spray, and blade spray (reduced water consumption by up to 50% and even stronger spray performance)
- Stop function - pause button to stop the water flow
- Automatic return to laminar spray
- Adjustable flow rate limiter
- 360° Swivel spout
- Nylon braided flex hoses
- Quick installation system
- 1.75gpm



PRODUCT FEATURES:



-  GROHE SilkMove®
-  GROHE StarLight®
-  GROHE QuickFix®

CERTIFICATIONS:



- ADA
- CEC Certified
- Low Lead Certified
- Cal Green Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- N/A
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

AVAILABLE FINISHES:

- 30205002**  GROHE StarLight® Chrome
- 30205DC2**  SuperSteel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

Tel: 1.630.582.7711 Fax: 1.630.582.7722

We reserve the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.grohe.us.

12-18-2020

PART OF **LIXIL**

30 205

LADYLUX® L2

SINGLE-HANDLE PULL DOWN KITCHEN
FAUCET TRIPLE SPRAY 1.75 GPM WITH
TOUCH TECHNOLOGY

Pure Freude
an Wasser



TECHNICAL DATA:

Product Height	14-15/16 in
Product Length	9-3/16 in
Product Width	6-1/4 in
Fitting Spout Height	8 in
Fitting Spout Reach	8-5/16 in
Fitting Handle Height	7-1/8 in
GPM (Min)-GPM (Max)	1.75 gal (US)/min
Fitting No of Holes Required	1

